



บริษัท น้ำมันอพลโล (ไทย) จำกัด
APOLLO (THAILAND) CO., LTD.



DAPHNE NEW PUNCH OIL

High performance Punch oil

1. Application

For use on punching of silicon steel plate in case of the oil existence is undesirable on the progressive work.

2. General

Very low viscosity volatile synthetic oil containing extreme pressure additive and rust preventive additive.

3. Characteristic

1. Good prolong the die life and finish fine surface.
2. Decrease "Burr" and good surface precision.
3. Excellent drying performance.
4. Excellent combustibility.
5. Very small smelling.
6. Excellent anti-rust performance.

4. Attention

Be careful about fire because of volatility.

5. Typical Specification

				ASTM
Density	@ 15 °C	g/c m ³	0.8728	D-4052
Color	ASTM		L0.5	D-1500
Flash point	P.M.	°C	52	D-92
	P.M.	°F	126	D-92
Viscosity	@ 40 °C	cSt	1.284	D-445
Acid number		mgKOH/g	0.08	D-974
Coefficient of friction	@ R.T.	μ	0.130	-

- Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or E-Mail : order@apollothai.com
- Due to continual product research and development, the information contained herein is subject to change without notification.

นิคมอุตสาหกรรมอมตะซิตี้ ชลบุรี 700/623 หมู่ที่ 4 ต.บ้านเก่า อ.พานทอง จ. ชลบุรี 20160 โทร. 0-3845-6900 แฟกซ์ 0-3821-0055

Amatanacity Chonburi Industrial Estate 700/623 Moo 4,Bankao, Panthong, Chonburi 20160 Tel : 038-456-900 Fax : 038-210-055 www.apollothai.com