



บริษัท น้ำมันอพลโล (ไทย) จำกัด  
APOLLO (THAILAND) CO., LTD.



# DAPHNE PRESS ER 68

## High performance Press drawing Oil

### 1. Application

This product is extensively used as press forming oil for pressing bodies of automobiles and machinery parts. Recommended for steel sheet which require short term rust preventive properties.

### 2. Quality

Highly refined mineral oil with good lubricity property.

### 3. Typical Specification

				<u>ASTM METHOD</u>
Density	@ 15°C	g/cm <sup>3</sup>	0.8835	D-1298
Color	ASTM		L 2.0	D-1500
Flash Point	COC	°C	244	D-92
Viscosity	@ 40°C	cSt	65.80	D-445
	@ 100°C	cSt	9.046	D-445
Viscosity Index			113	D-2270
Acid Number	Potentiometric	mgKOH/g	0.25	D-974

- Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or E-Mail : [order@apollothai.com](mailto:order@apollothai.com)
- Due to continual product research and development, the information contained herein is subject to change without notification.

นิคมอุตสาหกรรมอมตะซิตี้ ชลบุรี 700/623 หมู่ที่ 4 ต.บ้านเก่า อ.พานทอง จ. ชลบุรี 20160 โทร. 0-3845-6900 แฟกซ์ 0-3821-0055

Amatanacity Chonburi Industrial Estate 700/623 Moo 4,Bankao, Panthong, Chonburi 20160 Tel : 038-456-900 Fax : 038-210-055 www.apollothai.com