



บริษัท น้ำมันอพลโล (ไทย) จำกัด
APOLLO (THAILAND) CO., LTD.



DAPHNE HONING OIL HT

1. Application

Daphne Honing Oil HT is to be used as cutting oil for honing and lapping process.

2. Characteristic

Daphne Honing Oil HT is a very low viscosity cutting oil that can be expected excellent tool life and high-quality finished surface. Moreover, this oil is contains a special additive to improve the soaking and cleaning properties, so that it gives excellent machining ability.

3. Typical Specification

Density	@15°C	g/cm ³	0.8467
Color	ASTM		L0.5
Flash Point	(C.O.C.)	°C	102
Viscosity	@40 °C	mm ² /s	3.261
Total Acid Number		mgKOH/g	0.04

- Based on available information, this product is not expected to produce adverse effects on health when used for the intened application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or E-Mail : order@apollothai.com
- Due to continual product research and development, the information contained herein is subject to charge without notification.

นิคมอุตสาหกรรมอมตะซิตี้ ชลบุรี 700/623 หมู่ที่ 4 ต.บ้านเก่า อ.พานทอง จ. ชลบุรี 20160 โทร. 0-3845-6900 แฟกซ์ 0-3821-0055

Amatanacity Chonburi Industrial Estate 700/623 Moo 4,Bankao, Panthong, Chonburi 20160 Tel : 038-456-900 Fax : 038-210-055 www.apollothai.com