



บริษัท น้ำมันอพลโล (ไทย) จำกัด  
APOLLO (THAILAND) CO., LTD.



# DAPHNE SUPER BLANKING SR80

## High performance Press drawing oil

### 1. Application

Daphne Super Blanking SR80 is a special metal working oil especially for fine blanking. Excellent performance for hard metal such as stainless.

### 2. General

Non-chlorine type, combined with active sulfur agent and some fatty agents with high lubricity.

### 3. Characteristics

1. Environmental friendly due to non-chlorine type.
2. Excellent tool life.
3. Extend mold life due to high lubricity.
4. Widely applicable for working work piece such as carbon-steel, SK metal and Cr-Ni metal.

### 4. Typical Specification

				<u>ASTM</u>
Density	15 °C	g/cm <sup>3</sup>	0.926	D-1298
Flash Point	(C.O.C.)	°C	204	D-92
Viscosity	@ 40 °C	cSt	86.96	D-445
Sulphur content		wt%	3.67	-

### 5. Remark for usage

1. This oil contains active sulfur type EP agent to improve working performance. Hence it has some possibility to cause discoloration and corrosion for non-ferrous (especially Copper)
2. In case some skin irritation occurs, please wash the skin with soap and use the protect cream.

- Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or E-Mail : [order@apollothai.com](mailto:order@apollothai.com)
- Due to continual product research and development, the information contained herein is subject to change without notification.

นิคมอุตสาหกรรมอมตะซิตี้ ชลบุรี 700/623 หมู่ที่ 4 ต.บ้านเก่า อ.พานทอง จ. ชลบุรี 20160 โทร. 0-3845-6900 แฟกซ์ 0-3821-0055

Amatanacity Chonburi Industrial Estate 700/623 Moo 4,Bankao, Panthong, Chonburi 20160 Tel : 038-456-900 Fax : 038-210-055 www.apollothai.com