



บริษัท น้ำมันอพลโล (ไทย) จำกัด
APOLLO (THAILAND) CO., LTD.



DAPHNE PUNCH SU-P2

High performance Punch oil

1. Application

For use on punching and pressing of stainless steel and carbon steel plate in case of the oil existence is undesirable on the progressive work.

2. Quality

Semi-evaporate oil type very low viscosity synthetic oil containing extreme pressure and rust preventive additive.

3. Punching Ability

Optimum Thickness 0.1 – 1.0 mm. For stainless steel, carbon steel and steel alloy.

4. Typical Specification

				<u>ASTM</u>
Density	15 °C	g/cm ³	0.777	D-1290
Color	ASTM		L 0.5	D-1500
Flash Point	P.M.	° C	67	D-92
Viscosity	@ 40 °C	cSt	1.45	D-445
Acid Number		mgKOH/g	0.15	D-972

- Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or E-Mail : order@apollothai.com
- Due to continual product research and development, the information contained herein is subject to change without notification.

นิคมอุตสาหกรรมอมตะซิตี้ ชลบุรี 700/623 หมู่ที่ 4 ต.บ้านเก่า อ.พานทอง จ. ชลบุรี 20160 โทร. 0-3845-6900 แฟกซ์ 0-3821-0055

Amatanacity Chonburi Industrial Estate 700/623 Moo 4,Bankao, Panthong, Chonburi 20160 Tel : 038-456-900 Fax : 038-210-055 www.apollothai.com