



บริษัท น้ำมันอพลโล (ไทย) จำกัด
APOLLO (THAILAND) CO., LTD.



DAPHNE ALPHA GEAR OIL SERIES

High Performance Synthetic Gear Oil

1. Description

The premium quality gear oil formulated with synthetic base oil incorporating various additives such as special extreme pressure additives, oxidation inhibitor, rust prevention additive, anti-foaming and oiliness agents to provide excellent performance.

2. Application

Recommended for use as a lubricating oil for all kinds of reduction gear.

3. Characteristics

1. High viscosity Index and extremely low pour point.
2. Excellent oxidation stability - A combination of oxidation inhibitor and synthetic base oil assures excellent oxidation stability under severe/ high temperature operating condition and assures longer oil life.
3. Excellent anti-pitting, anti-wear & anti-seizure properties - Addition of special oiliness and extreme pressure agents give this oil excellent anti-pitting, anti-wear & anti-seizure properties which help to extend gear service life.
4. Excellent demulsibility - Extremely quick separation with water prevents formation of sludge and rust.
5. Excellent anti-corrosion & anti-rust properties - Effective rust preventive agent and corrosion inhibitor prevent corrosion caused by water and acid produced through deterioration process.
6. None corrosive to sealing Materials.
7. Clear/ transparent.

4. Typical specifications

			<u>68</u>	<u>100</u>	<u>150</u>	<u>220</u>	<u>320</u>	<u>ASTM Method</u>
Color	ASTM		L0.5	L0.5	L0.5	L0.5	L0.5	D-1500
Density	@15 °C	g/cm ³	0.8426	0.8439	0.8454	0.8471	0.8609	D-1298
Viscosity	@ 40 °C	mm ² /s	66.27	95.87	149.80	216.3	310.0	D-445
	@ 100 °C	mm ² /s	10.52	13.80	19.38	26.65	33.73	D-445
Viscosity Index			147	146	148	157	152	D-2270
Flash point	C.O.C	°C	252	254	258	290	302	D-92
Pour point		°C	-50>	-50>	-50>	-47.5	-42.5	D-97
Acid Number		mgKOH/g	0.39	0.40	0.41	0.44	0.45	D-974
Copper Corrosion	100 °C x 3 Hrs.		1(1b)	1(1b)	1(1b)	1(1b)	1(1b)	D-130

- Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or E-Mail : order@apollothai.com
- Due to continual product research and development, the information contained herein is subject to change without notification.

นิคมอุตสาหกรรมอมตะซิตี้ ชลบุรี 700/623 หมู่ที่ 4 ต.บ้านเก่า อ.พานทอง จ. ชลบุรี 20160 โทร. 0-3845-6900 แฟกซ์ 0-3821-0055

Amatanacity Chonburi Industrial Estate 700/623 Moo 4,Bankao, Panthong, Chonburi 20160 Tel : 038-456-900 Fax : 038-210-055 www.apollothai.com