



บริษัท น้ำมันอพลโล (ไทย) จำกัด
APOLLO (THAILAND) CO., LTD.



DAPHNE MECHANIC OIL 220

High Performance Multi Oil

1. Application

1. Multi-purpose lubricating oil of high performance, Suits best as hydraulic oil and lubricating oil for bearing and gear applications where load carrying ability, heat resistant property, stability and demulsibility are simultaneously required.
2. Lubricating oil for traction drives, such as Beyer and PIV type.

2. Quality

High quality lubricating oil refined by most advanced Hydro-Treating Process. Adding various additives.

3. Characteristics

1. High oil film strength and anti-oxidizing characteristics, especially in high temperatures.
2. High rust preventive, anti-foam characteristics, low friction property and good demulsibility.

4. Typical Specification

			220	ASTM
Specific Gravity	15/4	°C	0.8973	D1298
Color	ASTM		L1.5	D1500
Flash Point	C.O.C.	°C	262	D92
Viscosity	@ 40°C	cSt	222.2	D445
	@ 100°C	cSt	19.98	D445
Acid Number		mgKOH/g	0.56	D974
Copper Corrosion	100°Cx3		1(1a)	

- Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or E-Mail : order@apollothai.com
- Due to continual product research and development, the information contained herein is subject to change without notification.

นิคมอุตสาหกรรมอมตะซิตี้ ชลบุรี 700/623 หมู่ที่ 4 ต.บ้านเก่า อ.พานทอง จ. ชลบุรี 20160 โทร. 0-3845-6900 แฟกซ์ 0-3821-0055

Amatanacity Chonburi Industrial Estate 700/623 Moo 4, Bankao, Panthong, Chonburi 20160 Tel : 038-456-900 Fax : 038-210-055 www.apollothai.com