



บริษัท น้ำมันอพลโล (ไทย) จำกัด
APOLLO (THAILAND) CO., LTD.



DAPHNE CUT HL 25

1. Application

Daphne Cut HL 25 is to be used as a dielectric fluid in electrical discharge machines.

2. Quality

Daphne Cut HL 25 is high quality synthetic lubricating oil.

3. Characteristics

1. This oil is highly refined base oil and odorless.
2. Designed to prevent to be poisoned.
3. Low viscosity and high flash point.
4. As high flash point, this oil is preventable to fire.
5. As good stability, extend oil life.
6. As low viscosity, enables to remove chips easily.

4. Typical Specifications

Density			0.7890
Color	ASTM		L 0.5
Flash Point	P.M.	°C	88
Viscosity	@ 40 °C	mm ² /sec	2.560
Total Acid Number		mgKOH/g	0.01
Distillation	IBP	°C	206
	EP	°C	256

- Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or E-Mail : order@apollothai.com
- Due to continual product research and development, the information contained herein is subject to change without notification.

นิคมอุตสาหกรรมอมตะซิตี้ ชลบุรี 700/623 หมู่ที่ 4 ต.บ้านเก่า อ.พานทอง จ. ชลบุรี 20160 โทร. 0-3845-6900 แฟกซ์ 0-3821-0055

Amatanacity Chonburi Industrial Estate 700/623 Moo 4, Bankao, Panthong, Chonburi 20160 Tel : 038-456-900 Fax : 038-210-055 www.apollothai.com