



บริษัท น้ำมันอพลโล (ไทย) จำกัด
APOLLO (THAILAND) CO., LTD.



DAPHNE SUPER MULTI 2 M

High Performance Multi Oil

1. Application

Daphne Super Multi 2M is applied to main spindle of machining center in order to prevent displacement of main spindle.

2. General

It uses a high quality narrow cut paraffinic mineral base oil and contains various additives to provide the excellent performance.

3. Characteristics

1. High oxidation resistance gives longer oil life.
2. Especial extreme pressure additives give high-with stood load property.
3. Excellent rust preventive property.
4. Excellent anti-foam property.

4. Viscosity Grade and Oiling Methods

<u>Oil Grade</u>	<u>ISO Viscosity Grade</u>	<u>JIS Standard</u>
2 M	2	K 2239, ISO VG2

5. Typical Specification

			<u>Typical</u>	<u>ASTM Method</u>
Density	@ 15°C	g/cm ³	0.8153	D-1298
Color	ASTM		L 2.0	D-1500
Flash Point	C.O.C.	C°	98	D-92
Viscosity	@ 40 °C	mm ² / s	2.127	D-445
Acid Number		mgKOH/g	0.08	D-974
Copper Corrosion	100°Cx3 Hrs.		1b	D-130

- Based on available information, this product is not expected to produce adverse effects on health when used for the intened application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or E-Mail : order@apollothai.com
- Due to continual product research and development, the information contained herein is subject to charge without notification.

นิคมอุตสาหกรรมอมตะซิตี้ ชลบุรี 700/623 หมู่ที่ 4 ต.บ้านเก่า อ.พานทอง จ. ชลบุรี 20160 โทร. 0-3845-6900 แฟกซ์ 0-3821-0055

Amatanacity Chonburi Industrial Estate 700/623 Moo 4,Bankao, Panthong, Chonburi 20160 Tel : 038-456-900 Fax : 038-210-055 www.apollothai.com